Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SWIVEL6

Protect It! Surge Suppressor

Highlights

- 6 rotatable outlets
- Direct plug-in design
- 1200 joule rating
- Diagnostic LEDs
- $20,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

Description

The SWIVEL6 offers reliable surge and line noise protection. Premium features include a compact, direct plug-in design for easy portability, six rotatable outlets for easier plug connection and removal and 1200 joules of surge absorption protection. Diagnostic LEDs alert you to potential wiring or protection faults before connected equipment is damaged. Lifetime warranty with $20,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only).

Applications

- Ideal for any desktop, network or home computing application requiring AC protection.

Package Includes

- SWIVEL6 Surge Suppressor
- Instruction manual with warranty information

Features

- 6 rotatable outlets allow for easier plug connection and removal
- 1200 joule rating
- Direct plug-in design converts two outlets into six by pluggin into any wall outlet
- Diagnostic LEDs alert you to potential wiring or protection faults before connected equipment is damaged
- Lifetime warranty with $20,000 Ultimate Lifetime Insurance (USA & Canada Only)

Specifications

OVERVIEW	
Intended Application	Home/Office
SYSTEM OVERVIEW	
Voltage compatibility	120V AC
Frequency compatibility	60 Hz
OUTPUT	

Output volt amp capacity (amps)	15
Outlet quantity / type	6 NEMA 5-15R
Outlet orientation	Rotatable
INPUT	
Input connection type	NEMA 5-15P
Input cord length (ft.)	Direct plug-in
Recommended Electrical Service	120V (110-125V)
LEDS ALARMS & SWITCHES	
Diagnostic LEDs	Built-in LEDs confirm suppressor "protected" (green) and "grounded" (red) status
SURGE / NOISE SUPPRESSION	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC suppression joule rating	1200 joules
Clamping voltage (RMS)	330
AC suppression response time	< 1 ns
UL1499 let through rating	330V - UL Verified
EMI / RFI filtering	Up to 20 dB
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
PHYSICAL	
Shipping weight (lbs)	0.37
Shipping Dimensions (HWD/in)	13 x 6 x 19
Unit weight (lbs)	0.26
Unit Dimensions (HWD/in)	10.5 x 6 x 14
Material of construction	Plastic
Receptacle Color	Black
Style	Direct Plug-in
CERTIFICATIONS	
UL1449 1998 Rev. (AC Suppression)	UL1449
cUL / CSA (Canada)	cUL
Approvals	RoHS
WARRANTY	
Product Warranty Period	Lifetime
Connected Equipment Coverage	$20,000

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3617.

©2009 Tripp Lite. All Rights Reserved.